

FLUSHSOL[®]

CLEANSING AGENT

Removes scales, dust, dirt and unwanted residues from spray tanks and other containers.
Protects pumps and valves. Reduces strainer clogging.

MANUFACTURED BY:

NULANDIS, A DIVISION OF AECI LIMITED
PO Box 14418
WITFIELD
1467

UN number: 1759 – Corrosive solid n.o.s

Flushsol[®] is the registered trademark of AECI Limited (Nulandis, a division of AECI Ltd.)

DIRECTIONS FOR USE: USE ONLY AS INDICATED

Use 10 g per 10 ℓ, 100 g per 100 ℓ or total container in 500 ℓ of water. Dissolve the necessary amount of FLUSHSOL in part of the final volume of water first before adding the balance of water. Agitate thoroughly - in the case of spray rigs use agitator or by-pass for at least 15 minutes. Leave cleansing solution overnight in tank or container. Open boom valve in spray tank and pump solution out through boom or spray hoses. Rinse containers thoroughly with fresh water, or circulate clean water for 10 minutes and spray through boom or spray-hoses before re-using.

FLUSHSOL has no effect on steel, aluminium, brass, glass fibre, etc. Tanks and containers in extremely corroded conditions should not be cleaned with FLUSHSOL.